



GPS TRACKING SYSTEM

STB-403S

MINI PORTABLE ANDROID MAGNETIC STRIPE CARD READER



- ✓ COMPATIBLE WITH ANDROID SYSTEM;
- ✓ ALL 3 TRACKS CAN SET TO 75/210 BPI;
- ✓ USB OR SERIAL INTERFACE;
- ✓ LONG SERVICE LIFE (500,000 CARD PASSES);
- ✓ SUITABLE FOR ALL ISO7811/7812, ANSI, AAMVA AND CA DMV MAGNETIC CARDS;



Technical Specifications :



STB-403S



Dimension	90mm(L) x 26mm(W) x 28mm(H)		
Weight	85g(approx.)		
Power Supply	+5V DV ±5%		
Power consumption	40mA (max.)		
Operation Locus	Indoor use		
Card Standard	ISO7811/7812		
Track Position	ISO 1 (IATA)	ISO 2 (ABA)	ISO 3 (MINTS)
Recording Density	210 BPI	75 BPI	210 BPI
Recording Capacity	79 Characters (7bits)	40 Characters (5bits)	107 Characters (5bits)
Interface	USB / Serial		
Card Thickness	Plastic 0.76 ± 0.08mm		
Head Function	Read only 1.5mm		
Operation Speed	10 ~ 150cm/sec		
Life of Head	500,000 card passes (1 pass : one swipe)		
Error Rate	Less than 0.5% (JSE Test card)		
Temperature	Storage : -30°C to +70°C Operating : -20°C to +70°C		
Humidity	Storage : 0% to 95% RH Operating : 20% to 90% RH		

MASTERTECH INTERNATIONAL

40/13 Ngamwongwan23 Ngamwongwan Rd., Nontaburi 11000
www.mastertech.co.th

ฝ่ายขาย GPS
Tel. 02-952-7280-3 ต่อ 450,455,447
E-mail. gps@mastertech.co.th